LIST OF TABLES

| Table 1.1 | Reynolds number calculations for a size 2 (0.8 mm) Torch | 12 |
|-----------|---|----|
| Table 2.1 | Equilibrium compositions of an oxyacetylene flame for adiabatic temperatures at different gas ratios and at less than adiabatic flame temperatures | 26 |
| Table 3.1 | The organic compounds and aspects to be investigated | 47 |
| Table 4.1 | Summary of oxide thicknesses on the pre-growth surfaces for the different types of surface treatment techniques | 50 |
| Table 4.2 | Average Particle densities for the surface roughness treatments | 53 |
| Table 4.3 | Regions of highest diamond deposition for the different flame directions and tilt angles | 53 |
| Table 4.4 | Normalized particle densities for the grooved samples depending on flame direction and flow rate at a 0=30 degree tilt angle | 54 |
| Table 4.5 | Diamond particle densities for the scratched and/or HF dipped samples | 56 |
| Table 4.6 | Summary of oxide thicknesses, diamond particle size, and particle density for the pretreated samples and the control sample | 58 |
| Table 4.7 | Aspect of organic compound studied and nature of deposition | 62 |
| Table 5.1 | Angles of incidence for the upstream and downstream wall surfaces and their vertical and horizontal components for the different tilt angles (positive values signify below horizontal) | 68 |